

## DH(R)系列渣浆泵性能参数 Performance Parameter of Type DH(R) Slurry Pump

Type	Flow Rate	Head	Speed	Max Efficiency	NPSH	Inlet Diameter	Outlet Diameter	Max. Particle Size	Weight
	M3/h	m	R/min.	%	m	(mm)	(mm)	(mm)	(kg)
DG150×100-D	36-252	3.5-51	600-1400	30-50	2.5-3.5	150	100	82	460
DG200×150-E	137-576	10-48	800-1400	50-60	3-4.5	200	150	127	1120
DG250×200-S	216-979	13-50	500-1000	45-65	3-7.5	250	200	178	2285
DG300×250-G	360-1512	11-58	400-850	50-70	2-4.5	300	250	220	4450
DG350×300-G	504-3168	6-66	300-700	60-68	2-8	350	300	240	5400
DG450×400-T	864-3816	9-48	250-500	60-72	3-6	450	400	254	10800
DG250×200H-S	396-1296	10-80	500-950	60-72	2-5	250	200	180	3188
DG300×400H-T	612-2232	28-78	350-700	60-72	2-8	300	250	210	4638
DG400×350H-TU	720-3600	20-72	300-500	60-72	3-6	400	350	230	12250
DG250X200L	340-870	10-45	900	65-70	<4	250	200	178	2500
DG250X200MS	520-1000	38-65	850	70-74	<4	250	200	180	3000
DG300X250L	500-950	10-42	700	65-68	<4	300	250	220	3000
DG350X300L	700-2400	10-38	650	74-78	<4	350	300	241	6000
DG350X250M	500-1500	35-68	600	74-78	<4	350	250	220	3513
DG450X300M	900-2500	40-70	550	76-80	<4	450	300	241	3513
DG450X350M	1200-3500	40-70	550	71-75	<4	450	350	245	7300

DG500X450L	1200-3800	10-43	48	78-80	<4	500	450	354	7850
DG600X450MS	1500-4200	40-76	500	80	<4	600	450	354	7950
DG650X550L	1800-5500	10-48	420	83	<4	650	550	300	8000
DG650X500MS	2000-6000	35-73	440	85	<4	650	550	250	11300
DG700X600MS	2500-8000	30-76	470	85	<4	700	600	220	30000
DG760X700MS	2800-10000	30-76	380	81	<4	760	700	280	45000
DG800X700L	3000-8500	10-43	380	81	<4	800	700	280	23000
DG800X750MS	5500-14000	34-74	349	81	<4	800	750	290	55000
DG900X800L	4000-13000	10-40	280	85	<4	900	800	300	23000
DG900X850MS	7000-17000	34-74	330	85	<4	900	850	320	65000
DG1000X900MS	8000-20000	34-74	175	85	<4	1000	900	340	80000
DG1050X950L	7500-17000	10-38	258	85	<4	1050	950	345	95000
DG1200X1000MS	8000-28000	24-75	290	85-87	<4	1200	1000	350	121000